

10/ 713 418

Nov 03 05 10:25a

Camoriano & Assoc

502 426 1167

P.1

RECEIVED
CENTRAL FAX CENTER

Page 1 of 1

Certificate of Correction
Patent Number 6,955,380

NOV 03 2005

Certificate

NOV 08 2005

of Correction

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

U.S. Patent Number: 6,955,380 *B1*
Issue Date: October 18, 2005
Inventor(s): Sebastian Barr
Title: DRAWER SAFETY LATCH

Certificate of Transmission

I hereby certify that this correspondence is being facsimile transmitted to the United States Patent and Trademark Office, Fax No. (571) 273-8300 on November 3, 2005 (Date)

Name: CAROLYN LAUGHERTY Signature: Carolyn Laugherty

REQUEST FOR CERTIFICATE OF CORRECTION UNDER 35 U.S.C. 254

Attention Certificate of Corrections Branch
Commissioner for Patents
Post Office Box 1450
Alexandria, Virginia 22313-1450

Dear Sir:

Form PTO/SB/44 is provided with this facsimile transmittal to request a certificate of correction for the above referenced patent. The errors were caused by the Patent Office. Therefore, no fee is due. Thank You.

Respectfully submitted,

Theresa Camoriano

Theresa Fritz Camoriano
Reg. No. 30,038
Camoriano & Associates
8225 Shelbyville Road
Louisville, KY 40222
phone (502) 423-9850
fax (502) 426-1167

NOV 14 2005

PTO/SB/44 (04-05)

Approved for use through 04/30/2007. OMB 0851-0033

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.
(Also Form PTO-1050)**UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION**Page 1 of 2

PATENT NO. : 6,955,380 *B1*
APPLICATION NO.: 10/713,418
ISSUE DATE : 10/18/2005
INVENTOR(S) : Sebastian Barr

It is certified that an error appears or errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Columns 1 and 2:

The first three paragraphs of the Description of the Preferred Embodiment are in the wrong order. The order of the paragraphs should be reversed, and the text beginning at column 1, line 51 and ending at column 2, line 17 should be replaced with the following:

FIGS. 1-8 show a drawer safety latch 10 made in accordance with the present invention. Referring to FIGS. 2, 4, 5, and 6, the safety latch 10 is a substantially "L" shaped body (seen best in FIG. 6), including a vertical leg 12, a horizontal leg 36 projecting inwardly from said vertical leg 12, and an engaging arm 20 projecting forward from said horizontal leg 36. The vertical leg 12 lies in one plane, and the engaging arm 20 extends along a second plane that is parallel to and offset from the vertical leg.

The vertical leg 12 has an inside face 14, a flat outside face 16, and a top surface 18. In this embodiment 10, there is an adhesive strip adhered to the outside face 16, including a peel-off protective sheet 24, which covers the adhesive strip until the user is ready to install the safety latch 10 in the drawer 22, at which time he peels off the protective sheet 24 to expose the adhesive surface in order to adhere the vertical leg 12 to the side of the drawer 22.

The engaging arm 20 has a top surface including front and rear ramps 26, 28, which are collinear, and a trough 30 between the two ramps 26, 28. The trough 30 has substantially straight front and rear walls and defines an upward opening. Both of the ramps 26, 28 terminate short of that upward opening in a vertical plane, leaving the upward opening free to receive the front face of the cabinet, so the trough receives and abuts the front face of the cabinet and stops the travel of the drawer both when the drawer is opening and when the drawer is closing. As is explained in more detail later, the trough 30 has a depth which permits it to engage the front face of the cabinet 34 (see FIG. 3). The top surface of the front ramp 26 tapers from a lower elevation in front to a higher elevation in back, where it meets the trough 30. The top surface of the rear ramp 28 tapers from a higher elevation in front, where it meets the trough 30, to a lower elevation in back.

MAILING ADDRESS OF SENDER (Please do not use customer number below):

Camoriano & Associates
8225 Shelbyville Rd.
Louisville, KY 40222

This collection of information is required by 37 CFR 1.322, 1.323, and 1.324. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 1.0 hour to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Attention Certificate of Corrections Branch, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

NOV 14 2005

PTO/SB/44 (04-05)

Approved for use through 04/30/2007. OMB 0651-0033

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.
(Also Form PTO-1050)**UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION**Page 2 of 2

PATENT NO. : 6,955,380 B1

APPLICATION NO.: 10/713,418

ISSUE DATE : 10/18/2005

INVENTOR(S) : Sebastian Barr

It is certified that an error appears or errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 3, claim 1:

Replace entire claim 1 with the following:

1. A safety latch for a drawer, comprising:

an L-shaped body, including a vertical leg; and a horizontal leg projecting inwardly from said vertical leg; and an engaging arm projecting from said horizontal leg along a plane parallel to and offset from said vertical leg, said vertical leg having a flat outer surface for mounting to the inside of a drawer, and said engaging arm having a top surface defining forward and rear ramps and a trough between said forward and rear ramps, said trough defining an upward opening, and said ramps terminating short of said upward opening in a vertical plane;
wherein said engaging arm is movable up and down relative to said vertical leg.

MAILING ADDRESS OF SENDER (Please do not use customer number below):

Camoriano & Associates
8225 Shelbyville Rd.
Louisville, KY 40222

This collection of information is required by 37 CFR 1.322, 1.323, and 1.324. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 1.0 hour to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Attention Certificate of Corrections Branch, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

NOV 14 2005